



Mobil Super™ 3000 X2 5W-40

Mobil Passenger Vehicle Lube , Taiwan

Premium Fully Synthetic Passenger Vehicle Engine Oil

Product Description

The Mobil Super 3000 range of lubricants are ultra premium synthetic engine oils, designed to provide outstanding levels of protection and performance.

Features and Benefits

Mobil Super 3000 products are industry proven so you can trust you will get the performance you want from your vehicle.

Mobil Super 3000 X2 provides:

- Outstanding wear protection
- Outstanding engine cleanliness
- Outstanding high temperature protection
- Outstanding low temperature protection

Applications

Mobil Super 3000 products are formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. We particularly recommend Mobil Super 3000 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions
- Turbo-Chargers and Direct Injection engines
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following builder approvals:
MB-Approval 229.3
Porsche A40
RENAULT RN0710
RENAULT RN0700
VW 502 00
VW 505 00

This product has the following builder approvals:

Peugeot/Citroën Automobiles B71 2296

This product is recommended for use in applications requiring:

API CF

GM-LL-B-025

This product meets or exceeds the requirements of:

API SN

API SM

API SL

API SJ

ACEA A3/B3

ACEA A3/B4

Properties and Specifications

Property	
Grade	SAE 5W-40
Ash, Sulfated, mass%, ASTM D874	1
Density @ 15 C, g/ml, ASTM D4052	0.86
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	83
Pour Point, °C, ASTM D97	-42
Viscosity Index, ASTM D2270	174

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2020

ExxonMobil international Holding Inc. Taiwan Branch
6F, No 2, Section 1, Tun Hua South Road
Taipei Taiwan

+886 2 2734 6888

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved