



## Mobil Ultra 10W-40

Mobil Passenger Vehicle Lube , Ukraine

Premium Quality Multigrade Passenger Vehicle Engine Oil

### Product Description

Mobil Ultra 10W40 is a premium quality motor oil for many types of gasoline and Diesel vehicles.

### Features and Benefits

Mobil Ultra 10W-40 is formulated with a proprietary mixture of premium and super premium quality base oils with an additive technology delivering ver performance and engine protection under a variety of driving conditions. Mobil Ultra 10W-40 reduces engine wear with excellent high and low tempe performance.

### Applications

Mobil Ultra 10W-40 can be used in a variety of passenger vehicles , light trucks and vans, and for anyone seeking a dependable super premium quality product.

### Specifications and Approvals

This product is recommended by ExxonMobil for use in applications requiring:

MB 229.1

This product meets or exceeds the requirements of the following industry specification:

ACEA A3/B3

API SJ

API SL

API SM

API SN

API SN PLUS

### Properties and Specifications

Property	
Grade	SAE 10W-40
Ash, Sulfated, mass%, ASTM D874	1
Density @ 15.6 C, g/ml, ASTM D4052	0.87
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.6

Property	
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	13.2
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	88.7
Pour Point, °C, ASTM D97	-42
Viscosity Index, ASTM D2270	150

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2022

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

**ExxonMobil**

Exxon Mobil Esso XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved