



## MOBIL DELVAC MODERN 15W40 CNG/LNG

Mobil Commercial Vehicle Lube , United States

High Performance Heavy Duty Engine Oil for Spark Ignited CNG and LNG Fueled Trucks and Buses

### Product Description

Mobil Delvac Modern 15W-40 CNG/LNG is a high performance heavy duty engine oil formulated specifically for spark ignited CNG and LNG fueled truck and bus engines. It provides excellent performance in the challenging operating environments presented by CNG (Compressed Natural Gas) and LNG (Liquefied Natural Gas) and offers extended drain interval capability.

This product is backwards compatible to CES 20085.

### Features and Benefits

Features	Advantages and Potential Benefits
Thermal Stability and Oxidation/Nitration Control	Extended Drain Interval Capability
Advanced Wear Protection	Helps Towards Long Engine Life
Effective Detergency/Dispersancy	Engine Cleanliness
Optimized Ash Level	Helps Protect Against Excessive Valve Recession and Spark Plug Fouling
Shear Stability	Engine Durability

### Applications

Mobil Delvac Modern 15W-40 CNG/LNG is a high performance heavy duty engine oil formulated specifically for spark ignited CNG and LNG fueled truck and bus engines.

- Spark ignited CNG/LNG fueled stoichiometric and lean-burn engines
- Extended Drain Interval Capability
- Compatible with Exhaust Gas Recirculation (EGR) Systems, Three Way Catalysts, and other emissions reduction systems

### Specifications and Approvals

This product meets or exceeds the requirements of:
Cummins CES 20092

### Properties and Specifications

Property	
Grade	SAE 15W-40
Viscosity Index, ASTM D2270	145
Total Base Number, mgKOH/g, ASTM D2896	6.6

Property	
Pour Point, °C, ASTM D97	-39
Ash, Sulfated, mass%, ASTM D874	0.9
Density @ 15 C, g/ml, ASTM D1298	0.9651
Flash Point, Cleveland Open Cup, °C, ASTM D92	229
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.95
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	110.7

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2021

### Exxon Mobil Corporation

22777 Springwoods Village Parkway

Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil Esso XTO

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved