



Mobil Sawguide Oil 100

Mobil Industrial , United States

Sawguide Oil

Product Description

MOBIL SAWGUIDE OIL is specifically formulated to lubricate the thin saw blades of modern gang s and edgers.

The choice of viscosity grade depends on equipment type, lubricant delivery system design and amb temperatures. Your Mobil representative can assist in selecting the proper viscosity grade.

Features and Benefits

MOBIL SAWGUIDE OIL offers the following features and benefits:

| Features | Benefits |
|---|---|
| Forms a highly effective friction-reducing film between the blade and the guide. This reduces operating temperature, which, in turn, reduces cooling-water requirements. | Drier sawdust |
| The buildup of pitch, or wood resin, on the blade and sawguide increases friction and accelerates wear. MOBIL SAWGUIDE OIL is uniquely formulated to reduce and control pitch buildup by optimizing lubricant solvency. | Provides outstanding control of friction and wear |
| Clings tenaciously to blade and guide surfaces, reliably protecting against the damaging metal-to-metal contact that causes wear. | Superb wear protection |
| Contains a potent anti-rust additive to protect blade surfaces from rust that would otherwise stain lumber surfaces. | Protects against rust |
| Formulated with tackiness additives that reduce the amount of oil thrown off the blades or blown off by air/water sprays. | Controls stray mist |

Applications

MOBIL SAWGUIDE OIL is specially formulated to meet the lubrication requirements of modern g

saws and edgers.

Typical Properties

| | |
|--|------------|
| MOBIL SAWGUIDE OIL | 100 |
| Color | 1.0 |
| Flash Point, °C | 219 |
| Density @ 15°C, kg/l | 0.882 |
| Kinematic Viscosity | |
| cSt @ 40°C | 100 |
| cSt @ 100°C | 11.8 |
| Pour Point, °C | -24 |
| Free Water, ppm | |
| @ 54°C | 37 |
| @ 82°C | - |
| Rust Prevention | Pass |
| Falex Wear, mg (low load, 600 lb for 2.5 hr) | 16 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via internet. This product should not be used for purposes other than its intended use. If disposing of this product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Sawguide are trademarks of Exxon Mobil Corporation or one of its subsidiaries.

05-2020

Exxon Mobil Corporation

22777 Springwoods Village Parkway

Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Exxon, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved