



## Mobil Vaprotec Light

Mobil Industrial , United States

Rust-Inhibiting Circulation Oil

### Product Description

Mobil Vaprotec Light is an ISO Viscosity Grade 32, turbine-quality circulation oil containing anti-oxidants and defoamants. It is enhanced with a three-phase rust inhibitor to protect surfaces lightly coated with oil; a liquid phase inhibitor to protect surfaces submerged in oil; and vapor space inhibitors to protect surfaces exposed to oil vapors.

### Features and Benefits

- Wide-temperature-range rust protection for steel surfaces in the vapor (air) spaces which do not come into contact with the oil
- Rust protection for metal surfaces where the oil has drained off, leaving only a thin film
- Rust protection for surfaces which are submerged in the oil
- Good corrosion protection for nonferrous metals
- Demulsibility equivalent to that of a normal turbine oil
- Superior oxidation stability
- Wide range of application

### Applications

Mobil Vaprotec Light is recommended for all applications requiring an ISO Viscosity Grade 32, turbine-quality oil with additional rust protection properties. Operation of systems with oil temperatures above 120°F will deplete the vapor phase inhibitors.

### Typical Properties

<b>Mobil Vaprotec Light</b>	
Product Number	60031-2
Specific Gravity	0.875
Color, ASTM D 1500	1.5
Pour Point, °C (°F)	-7 (20)
Flash Point, ASTM D 92, °C (°F), min	193 (380)
Viscosity	
cSt at 40°C	30
cSt at 100°C	5.3
Viscosity Index	95
TAN, ASTM D 664	0.4
Demulsibility, ASTM D 1401, ml after 30 min	0
Rust Protection, ASTM D 665	
Distilled Water	Pass
Synthetic Sea Water	Pass

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

### Exxon Mobil Corporation

22777 Springwoods Village Parkway  
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved