



Mobil Super X0

Mobil Passenger Vehicle Lube , United States

Mobil Super X0

Product Description

Mobil Super X0 Oils are formulated from high quality base stocks combined with modern performance additives to give your engine the proven protection and performance you expect under a wide variety of operating conditions for long engine life. This advanced technology lubricant contains performance additives to help protect engines for 7,500 kilometers between oil changes or 6 months, whichever comes first.

Mobil Super X0 Oils are available in three multi-viscosity grades: SAE 10W-30 (API SN/ILSAC GF-5), 15W-40 (API SN) , 20W-50 (API SN). Those claims are backward compatible with earlier performance levels such as API SM, SL, and SJ and previous ILSAC categories.

Features and Benefits

- Helps extend engine life
- Proven protection of critical engine parts for 7,500 kilometers or 6 months, whichever comes first*
- Excellent engine cleanliness
- Engine protection under a wide variety of operating conditions
- Helps reduce engine wear and deposits
- Meets or exceeds the latest industry specification (ILSAC GF-5 / API SN: Mobil Super 10W-30 and API SN : Mobil Super 15W-40 and 20W-50)

* The possibility of extending the times between oil changes does not apply under the following conditions: automobile races and commercial use, frequent haulage or cargo transport, excessive dirt or frequent operation in lowest gear. If your vehicle is covered by a warranty, follow the recommended oil change interval

Applications

Mobil Super X0 Oils are recommended for gasoline fueled automobiles and light duty trucks requiring an API SN, SM, SL or SJ. Mobil Super 10W-30 also meets ILSAC GF-5 (Starburst Certification Symbol).

Mobil Super X0 20W-50 has a higher viscosity which provides engines with full protection under higher operating speeds, higher ambient temperatures, and other adverse conditions.

Before using a Mobil Super X0 motor oils, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

Specifications and Approvals

This product meets or exceeds the requirements of :	10W-30	15W-40	20W-50
API SL	X	X	X
API SM	X	X	X
API SN	X	X	X
API SJ	X	X	X

This product is recommended for use in applications requiring:	10W-30	15W-40	20W-50
GM 6094M	X		

Typical Properties

Mobil Super X0	10W-30	15W-40	20W-50
API Service Classification	SN	SN	SN
Gravity, API	31.3	30.2	27.4
Specific Gravity	0.8692	0.8750	0.890
Pour Point, °C (°F)	-33(-27)	-30(-22)	-27(-17)
Flash Point, °C (°F), ASTM D 92	220(428)	237(459)	200(392)
Viscosity			
cSt at 40°C	69.4	108.1	162
cSt at 100°C	10.6	14.9	18.1
CCS, cP	6430@-25 °C	5369@-20C	8200@-15°C
MRV, cP	19,892@-30 °C	19800@-25°C	24,000@-20°C
Viscosity Index	141	143	124
Resource Conserving	YES	NO	NO

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2024

Exxon Mobil Corporation


22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved