



## MOBIL 1™ C40 GT 0W-40

Mobil Passenger Vehicle Lube , United States

Advanced Full Synthetic Engine Oil

### Product Description

Mobil 1™ C40 GT 0W-40 is an advanced full synthetic engine oil specifically engineered for high performing Porsche GT Engines. Mobil 1 C40 GT 0W-40 has been designed to protect the engine from wear in high temperature conditions and prevents deposits and sludge formation. It is the latest technology developed within the framework of the collaboration established with Porsche AG for over the last 30 years.

### Features and Benefits

Mobil 1 C40 GT 0W-40 is made with a proprietary blend of leading edge components formulated to be fully compatible with Porsche GT engines. Mobil 1™ C40 GT 0W-40 has been designed to help deliver excellent performance and protection in high temperature conditions. It is distinguishable by its unique green color. Key features and potential benefits(1) include:

Features	Advantages and Potential Benefits
Active cleaning agents	Contributes to deliver excellent engine cleanliness and sludge control
Excellent high-temperature thermal and oxidation stability	Helps to reduce oil aging for protection throughout your oil drain interval
High temperature oil film resistance	Contributes to excellent wear protection
Enhanced frictional properties	Helps improve fuel economy(2)

### Applications

Mobil 1 C40 GT 0W-40 is specifically designed for Porsche GT engines requiring C40 GT specification(3). Mobil 1 C40 GT 0W-40 is required by Porsche for the following models:

- 911 GT3 (991 and newer)
- 911 GT3 Cup (991/992)
- 911 GT3 R (991/992)
- 911 GT3 RS (991 and newer)
- 911 RSR (991)
- 911 R (991)
- 911 Speedster (991)
- 911 S/T (992)
- 718 Cayman GT4 RS (982)
- 718 Cayman GT4 RS Clubsport (982)
- 718 Spyder RS (982)

Mobil 1 C40 GT 0W-40 is not suitable for Porsche vehicles requiring an A40, C20, C30 or C40 approved Mobil 1 engine oils.

### Notes

(1): Based on industry and OEM standard engine tests.

(2): Actual savings are dependent upon vehicle and engine type, outside temperature and barometric pressure, driving conditions and your current engine oil viscosity.

(3): Always consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and specifications.

### Specifications and Approvals

<b>This product has the following approvals:</b>
Porsche C40 GT

### Properties and Specifications

Property	
Grade	SAE 0W-40
Viscosity Index, ASTM D2270	199
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	72
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	13.8
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 <sup>(6)</sup> sec <sup>(-1)</sup> , mPa.s, ASTM D4683	3.8
Density @ 15 C, g/ml, ASTM D1298	0.846
Flash Point, Cleveland Open Cup, °C, DIN EN ISO 2592	230
Pour Point, °C, ASTM D97	-48

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2024

### Exxon Mobil Corporation

22777 Springwoods Village Parkway  
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved