



## Mobil Special 30

Mobil Passenger Vehicle Lube , United States

Added Performance Engine Oil

### Product Description

Mobil Special 30 is a heavy duty engine oil primarily intended for use in gasoline automotive engines of passenger cars where a monograde motor oil SAE 30 meeting or exceeding an API SN, SM, SL or SJ is recommended. Formulated from high quality mineral base oils and an advanced additive system required for combustion engines contains an effective balance of detergents and dispersants to minimize the formation of sludge and deposits, retain alkalinity (TBN) and reduce wear.

### Features and Benefits

- Help promote engine cleanliness.
- Good protection against wear and corrosion.
- Low oil consumption.
- Guaranteed protection with the Mobil Special Limited Warranty.\*

\*Some limitations apply. For more specific details see the Mobil Special Limited Warranty available at [www.mobil.com/guarantee](http://www.mobil.com/guarantee).

### Applications

Mobil Special 30 is recommended for the lubrication of gasoline engines for passenger cars where a monograde motor oil SAE 30 meeting or exceeding an API SN, SM, SL or SJ is recommended. Can also be used in gear and hydraulic applications if the builder approves the use of monograde engine oil for these applications.

### Specifications and Approvals

Mobil Special meets or exceeds the requirements of:	SAE 30
API SN, SM, SL, SJ	X

### Typical Properties

Mobil Special properties	
SAE Grade	SAE 30
Viscosity @ 100°C, cSt, ASTM D 445	10.6
Total Base Number, mg KOH/g, ASTM 2896	7.2
Sulfated Ash, wt %, ASTM D 874	0.79
Flash Point, °C, ASTM D 92	230
Pour Point, °C, ASTM D 97	-36

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the

recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Mobil, the Mobil logotype and the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

#### Exxon Mobil Corporation

22777 Springwoods Village Parkway

Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved