



Mobil™ Transmission Fluid 75W

Mobil Commercial Vehicle Lube , Uruguay

Mobil passenger-vehicle-lube , Brazil, Argentina, Paraguay,Uruguay, Bolivia. Manual Automotive Transmission Fluid.

Product Description

Mobil™ Transmission Fluid 75W is a high performance gear oil blended from high quality mineral base oils and an advanced additive system.

Features and Benefits

Mobil™ Transmission Fluid 75W is resistant to high temperature and protects from oxidation, which provides excellent cold flow and smooth gear shifting.

Applications

Recommended by ExxonMobil for use in:

- On-highway light and heavy duty trucks, busses, and van transmissions where SAE 75W is required

Specifications and Approvals

This product meets or exceeds the requirements of:

API GL-4

Synchronized light duty manual transmissions.

BMW MTF LT-2

BMW MTF LT-3

BMW MTF LT4

BOT 350 M3

FIAT MZ1

FIAT MZ6

FIAT MZ7

Ford WSD-M2C200-C

Ford M2C 186-A

Ford WSS-M2C200-D2 (6DCT250 dry DCT)

GM W16612

GM 1940004 / 19259104 (BOT 303)

This product meets or exceeds the requirements of:**API GL-4**

GM 1940182

GM 1940764

GM 1940768

GM 1940768

NISSAN MT-XZ

NISSAN MT-XZ TL (JR Type)

PSA B71 2310

PSA B71 2330 (EZL 848)

PSA B71 2315

PSA B71 2316 (HBVFE)

PSA 9730 A8

Renault DC4 DW5 (6DCT250 dry DCT)

Special gear oil, MTF 94

Special Honda MTF

Special Honda MTF-II

Special Honda MTF-III

Tranself NFJ

Tranself NFP

Tranself NFX

Tranself TRJ

Tranself TRT

Tranself TRZ

Tranself TRP

Tranself TRX

Volvo 97308

Volvo 97309

VW G 009 317

This product meets or exceeds the requirements of:**API GL-4**

VW G 052 171

VW G 052 178

VW G 052 512

VW G 055 512 A2

VW G 052 726

VW G 060 726

VW G 50

VW GO 52 527 A2

VW GO 70 726 A2

VW G 052 549 A2

VW G 009 317

VW G 052 171

VW G 052 178

VW G 052 512

VW G 055 512 A2

VW G 052 726

VW G 060 726

VW G 50

VW GO 52 527 A2

VW GO 70 726 A2

VW G 052 549 A2

Properties and Specifications

Property	
Grade	SAE 75W
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	6.9
Flash Point, Cleveland Open Cup, °C, ASTM D92	231

Property	
Density @ 15 C, g/ml, ASTM D4052	0.85
Pour Point, °C, ASTM D97	-45
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	37

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

DISA Montevideo S.A. - San Fructuoso, 927, Montevideo - Centro Técnico (598) 22009920 interno 55175, en caso de derrames

(598) 22007185.

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved