



Mobilube™ XHP 75W-90

Mobil Commercial Vehicle Lube , Vietnam

Manual Automotive Transmission Fluid

Product Description

Mobilube XHP 75W-90 is an extra high performance manual transmission lubricant engineered for the latest heavy duty manual transmissions used in on highway commercial vehicles and cars. This transmission lubricant is designed using select base oils and an advanced additive package that enhances shifting performance, low temperature fluidity, and high temperature viscosity retention. Mobilube XHP 75W-90 is formulated with extended performance reserve for applications requiring API GL-4 service.

Features and Benefits

Today's technology has vastly improved the performance capabilities of on highway vehicle load, speed, and control through innovative drivetrain designs. These designs have increased the requirements of lubricants to deliver a higher level of performance. For heavy duty manual transmissions, friction control, wear reduction, thermal stability, shear stability, rust and corrosion inhibition, and seal protection are features that must be optimally balanced to provide extended gear and synchroniser life, smooth shift control, fuel economy, and high load capability over a wide range of applications. Mobilube XHP 75W-90 delivers excellent performance in current as well as older model manual transmissions. The key benefits include:

Features	Advantages and Potential Benefits
Excellent load carrying, anti-wear, and extreme pressure performance	Extended transmission life and reduced operating costs
Excellent protection against deposit and lacquer formation	Longer seal life with extended drain and service intervals
Maximum protection from corrosion of copper and its alloys	Protects and extends the life of synchronisers while delivering smoother shifting performance
Effective thermal and oxidation protection at high operating temperatures	Reduces wear and maintenance costs
Excellent shear stability	Maintains effective viscosity and film strength during severe operation
Very good low-temperature fluidity	Easier, smoother shifting, and quicker starts
Extended service capability	Lower operating costs and higher productivity

Applications

Recommended by ExxonMobil for use in:

- Heavy duty manual transmissions and gear cases where API GL-3/4 level performance is required.
- Passenger cars, on highway light and heavy duty trucks, busses, and vans.
- Where extended service and warranties are required.

Specifications and Approvals

This product is recommended by ExxonMobil for use in applications requiring:
API GL-4

Properties and Specifications

Property	
Grade	SAE 75W-90
Viscosity Index, ASTM D2270	158
Pour Point, °C, ASTM D97	-42
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	99
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	15
Flash Point, °C, ASTM D92	180
Density @ 15 C, g/ml, ASTM D4052	0.86
Shear Stability (KRL 20h), mm ² /s, CEC L-45-A-99	13.5

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.


04-2024

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved