



Mobil 1™ FS 0W-40

Mobil Passenger Vehicle Lube , Yemen

Advanced Fully Synthetic Engine Oil

Product Description

Mobil 1™ is the world's leading synthetic motor oil brand delivering our ultimate performance and protection.

Mobil 1™ FS 0W-40 advanced full synthetic engine oil is engineered for the latest gasoline and diesel engine technology (without Gasoline or Diesel Particulate Filters) delivering excellent all-round performance. It provides exceptional cleaning power, wear protection. Mobil 1™ FS 0W-40 keeps your engine running like new in all driving conditions.

Features and Benefits

Mobil 1™ FS 0W-40 is made with a proprietary blend of ultra high performance synthetic basestocks fortified with a precisely balanced component system.

- Meets or exceeds the latest OEM and industry standards
- Provides excellent overall performance
- Has excellent low temperature capabilities for rapid engine protection at start-up
- Has enhanced frictional properties that aids fuel economy
- Delivers fast protection for reduced engine wear and deposits even in the most extreme driving conditions
- Provides exceptional cleaning power for dirty engines.

Applications

Thanks to extensive cooperative development work with major manufacturers and the application of the latest lubrication technology, Mobil 1™ FS 0W-40 is recommended for many types of modern vehicles where it will help provide unsurpassed performance even under very demanding driving conditions.

- Latest engine technologies including Turbo-chargers, Direct Injection, Diesels (without DPF) and Hybrids
- High performance engines
- Most operating conditions, from mild to extreme

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
MB-Approval 229.5
MB-Approval 229.3
Porsche A40

This product has the following approvals:

VW 502 00

VW 505 00

AVTOVAZ (LADA cars)

Nissan Genuine Performances

BMW Longlife 01

This product is recommended for use in applications requiring:

API CF

VW 503 01

This product meets or exceeds the requirements of:

AAE (STO 003) Group B7

API SJ

API SL

API SM

API SN

API SN PLUS

API SP

ACEA A3/B4

Ford WSS-M2C937-A

Fiat 9.55535-M2

Properties and Specifications

Property	
Grade	SAE 0W-40
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	78,3
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13,8
Density @ 15.6 C, g/ml, ASTM D4052	0,841

Property	
Viscosity Index, ASTM D2270	182
Pour Point, °C, ASTM D97	-42


Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2024

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved