Mobil Special 2T™

Mobil Passenger Vehicle Lube , Hong Kong

高性能二衝程引擎機油

產品說明

Mobil Special 2T 是高性能的二衝程引擎機油，適用於機車、雪地車和稀薄機油/燃油比電鋸。Mobil Special 2T 經過預先稀釋，能確保與燃油快速混合。

特色與效益

Mobil Special 2T 結合高品質礦物油和優異的添加劑系統，提供良好的整體清潔表現與性能。主要特性與效益包括：

特性	優點與潛在效益
優異的磨損防護	延長引擎使用壽命
優異的熱能與氧化穩定性和積垢控制力	保持引擎潔淨，有效延長火星塞和油閥的使用壽命、防止活塞環黏結和活塞緊縮，並且抑制預燃問題
良好的抗腐蝕防護特性	延長引擎使用壽命
減少預燃現象	提升燃油效率並延長活塞使用壽命

應用範圍

Exxonmobil 建議將 Mobil Special 2T 用於 JASO FB 等級性能的二衝程引擎。

規格與認證

此產品符合或超越以下規範標準：
JASO FB

特性及規格

特性	
40°C 下的運動黏度，mm2/s，ASTM D445	66
100°C 下的運動黏度，mm2/s，ASTM D445	8.9
黏度指數，ASTM D2270	109
硫酸灰份，質量 %，ASTM D874	0.03
15°C 下的密度，g/ml，ASTM D4052	0.878
流動點，°C，ASTM D97	-6
閃火點，潘-馬氏閉杯，°C, ASTM D93	110

健康與安全

如需有關本產品的健康與安全建議，請參閱材料安全資料表 (MSDS)，其網址為：http://www.msds.exxonmobil.com/psims/psims.aspx

除非另有提及，否則此處使用的所有商標皆為 Exxon Mobil Corporation 或其子公司的商標或註冊商標。

05-2023

ExxonMobil Hong Kong
22nd Floor, Central Plaza,
18 Harbour Road, Wanchai
Hong Kong

+852 3197 8888
http://www.exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved