



Mobil Super Moto™ 10W-30

Mobil Passenger Vehicle Lube , Hong Kong

合成技術四行程機車引擎機油

產品說明

Mobil Super Moto™ 10W-30 是一款特別為現代機車引擎設計的高效能機油。這款機油專為最新引擎技術而研發，同時也能為採用傳統技術的引擎提供良好的保護，而且配合由各大主要車廠所引領的機車引擎技術發展趨勢。熱活化抗磨分子（Heat-Activated Anti-Wear Molecule™）能提供即時引擎保護，可使引擎免受其開動時造成的磨損，以及因長時間連續駕駛而造成高溫環境的影響。

特性與效益

Mobil Super Moto™ 10W-30 是一款四行程機車引擎機油，由 Mobil 1 的開發團隊結合採用合成技術及最新的 API SL 先進添加劑技術製作而成。這款機油的磨損防護效能提升 57% 以上*，可以延長機車引擎的壽命並提高燃油效益。

Mobil Super Moto™ 10W-30 擁有高牽引力，可防止離合器打滑。

熱活化抗磨分子 (Heat-Activated Anti-Wear Molecule™) 有助在高溫下保持機油黏度，防止引擎磨損。

*在行業標準引擎測試 Sequence IVA 的 API SL 方面，磨損防護表現相比業界標準的優勝超過 57%。

特性	優勢和潛在效益
合成技術	先進配方，在極端條件下亦可提供出色效能
引擎防護效能提升 57%	為引擎、變速箱和離合器提供三重防護
延長引擎壽命	出色的防磨損、潔淨和防腐蝕效能
熱活化抗磨分子 (Heat-Activated Anti-Wear Molecule™)	有助在高溫下保持機油黏度，防止引擎磨損

應用範圍

最適合需要按照車廠所建議的 API SL 等級，或使用 JASO MA/MA2 等級機油的現代四行程機車引擎。

規格與認證

本產品符合或超越以下要求：
API SL
JASO MA
JASO MA2

屬性和規格

屬性	
等級	SAE 10W-30
總鹼值, mgKOH/g, ASTM D2896	5.5
黏度指數, ASTM D2270	140
15°C 條件下的密度, g/ml, ASTM D4052	0.88
閃火點, 克利夫蘭開口杯, °C, ASTM D92	220
硫酸灰分, 重量%, ASTM D874	0.8
150°C 條件下的高溫高剪切黏度, mPa.s, ASTM D4683	3.2
100°C 條件下的運動黏度, mm2/s, ASTM D445	10.5
40°C 條件下的運動黏度, mm2/s, ASTM D445	71
流動點, °C, ASTM D97	-25
微型旋轉黏度計, 表觀黏度, -30 C, mPa.s, ASTM D4684	20000

健康和安全

如需了解本產品的健康與安全建議, 請參閱物質安全資料表 (SDS): <http://www.msds.exxonmobil.com/psims/psims.aspx>

除非另有說明, 否則此處使用的所有商標均為埃克森美孚公司或其子公司的商標或註冊商標

03-2022
ExxonMobil Hong Kong
22nd Floor, Central Plaza,
18 Harbour Road, Wanchai
Hong Kong

+852 3197 8888
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTOMOT

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved