



Mobil Super 3000 Formula R 5W-30

Mobil Passenger Vehicle Lube , Hong Kong

全合成引擎機油

產品描述

美孚 Super™ 3000 機油系列是合成型引擎機油，可提供卓越保護。

美孚 Super 3000 Formula R 5W-30 是一款高性能低灰分引擎機油，旨在延長引擎壽命，並維持柴油和汽油驅動客用車、輕型商用車及客貨車的廢氣減排系統之運作效率。

建議將本產品用於要求使用 RN0720 認證機油的雷諾汽車，以及需要使用符合或超越 ACEA C4 要求機油的各款歐洲汽車和輕型商用車。

特性及效益

- 有助於保持汽柴油車輛排放廢氣減排系統的效率。
- 可在高溫下獲得更長的運行時間，油品無氧化變稠和故障等問題。
- 低溫下具備卓越的流動性，確保冬季易於啟動以及油品在引擎內的快速循環流動。
- 適用於配備汽油和柴油引擎的乘用車與輕型商用車。

規格與認證

本產品已獲得下列認證：
RENAULT RN0720
MB-Approval 226.51
本產品建議用於需符合以下規範的應用案例：
FIAT 9.55535-S4
此產品滿足或超越以下要求：
ACEA C4

典型特性

Mobil Super 3000 Formula R 5W-30	
黏度, ASTM D 445	
cSt @ 40°C	73.8
cSt @ 100°C	12.4
硫酸灰分, wt%, ASTM D 874	0.5

Mobil Super 3000 Formula R 5W-30	
磷	0.05
閃火點, °C, ASTM D93	244
密度 @15° C kg/l, ASTM D 4052	0.85
流動點, °C, ASTM D 97	-36

健康與安全

如需有關此產品的健康與安全建議，請參閱材料安全資料表 (MSDS)，其網址為：<http://www.msds.exxonmobil.com/psims/psims.aspx>

除非另有提及，否則此處使用的所有商標皆為 Exxon Mobil Corporation 或其子公司的商標或註冊商標。

12-2021
ExxonMobil Hong Kong
22nd Floor, Central Plaza,
18 Harbour Road, Wanchai
Hong Kong
+852 3197 8888
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved