



Mobil Super Moto™ 15W-40

Mobil Passenger Vehicle Lube , Hong Kong

合成技術四行程機車引擎機油

產品說明

Mobil Super Moto™ 15W-40 是一款擁有高性能的現代機車引擎機油。Mobil Super Moto™ 15W-40 專為最新引擎技術而研發，同時能為採用傳統技術的引擎提供全面的保護，並符合主要車廠訂立的機車引擎技術發展趨勢。熱活化抗磨分子 (Heat-Activated Anti-Wear Molecule™) 能提供即時引擎保護，可使引擎免受引擎開動時的磨損，以及因長時間連續駕駛引起的高溫環境所影響。

特性與效益

Mobil Super Moto™ 15W-40 是一款四行程機車引擎機油，由 Mobil 1 的開發團隊結合採用合成技術及最新的 API SL 先進添加劑技術製作而成。產品的優質礦物油和添加劑比例精準平衡，能夠保持引擎清潔且免受腐蝕，只需一個系統循環油便可同時保護引擎和齒輪箱。

Mobil Super Moto™ 15W-40 擁有高牽引力，可防止離合器打滑。

熱活化抗磨分子 (Heat-Activated Anti-Wear Molecule™) 能夠提供即時引擎保護。

在行業標準引擎測試 Sequence IVA 的 API SL 方面，磨損防護表現相比業界標準的優勝超過 57%。

特性	優勢和潛在效益
合成技術	先進配方，在極端條件下亦可提供出色效能
引擎防護效能提升 57%	為引擎、變速箱和離合器提供三重防護
延長引擎壽命	出色的防磨損、潔淨和防腐蝕效能
熱活化抗磨分子 (Heat-Activated Anti-Wear Molecule™)	有助在高溫下保持機油黏度，防止引擎磨損

應用範圍

最適合符合車廠所建議的 JASO MA/MA2 要求的現代四行程機車引擎。

可為 JASO MA 或 JASO MA2 推出前所生產的機車引擎提供良好的保護。

規格與認證

產品符合或超越以下要求：
API SL
JASO MA
JASO MA2

屬性和規格

屬性	
等級	SAE 15W-40
流動點, °C, ASTM D97	-30

屬性	
15°C 條件下的密度, g/ml, ASTM D4052	0.88
總鹼值, mgKOH/g, ASTM D2896	5.5
100°C 條件下的運動黏度, mm2/s, ASTM D445	13.7
微型旋轉黏度計, 表觀黏度, -25 C, mPa.s, ASTM D4684	25000
黏度指數, ASTM D2270	140
40°C 條件下的運動黏度, mm2/s, ASTM D445	99
150°C 條件下的高溫高剪切黏度, mPa.s, ASTM D4683	4
閃火點, 克利夫蘭開口杯, °C, ASTM D92	230
硫酸灰分, 重量%, ASTM D874	0.8

健康和安全

如需了解本產品的健康與安全建議，請參閱物質安全資料表 (SDS): <http://www.msds.exxonmobil.com/psims/psims.aspx>
除非另有說明，否則此處使用的所有商標均為埃克森美孚公司或其子公司的商標或註冊商標。

03-2022
ExxonMobil Hong Kong
22nd Floor, Central Plaza,
18 Harbour Road, Wanchai
Hong Kong

+852 3197 8888
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved